MERCADIER®
Teintes & Matières

Information and Technical Support:
export@mercadier-group.com

APPLICATION OF COLOURED CONCRETE EBC or TROWELLED CONCRETE

SUPPORT

PLASTERBOARDS	MELAMINE LAMINATE WOODS	CEMENT MORTAR CONCRETE PATCHING COMPOUND	PLASTER GYPSUM TILES CEMENT BOARDS (FERMACELL ETC.) AERATED CONCRETE	ANHYDRITE SCREED	TILES	SHOWER WASH-BASIN BATH	« Ready to TILE » Ideally our products should be accompanied by products of our partner LAZER (if another brand*, contact us)

PRIMERS

ACRYLIC PRIMER (Mercadier paint)	TEXTURED ALL-SURFACE PRIMER		TEXTURED ALL-SURFACE PRIMER diluted at 20%	TEXTURED ALL-SURFACE PRIMER: 2 layers: 1st diluted at 20%, 2nd pure	TEXTURED ALL-SURFACE PRIMER	LIQUID WATERPROOFING PRIMER (2 layers)	When used on floors, it is advised to lay inexpensive tiles in order to stabilise and harden the suface before placing the Trowelled Concrete System
24H DRYING	30' TO 1H DRYING	30' TO 1H DRYING	30' TO 1H DRYING	2nd layer when 1st is dry; 1H to 5H DRYING for 2nd	30' TO 1H DRYING	30' DRYING	

APPLICATION OF COLOURED CONCRETE EBC OR TROWELLED CONCRETE

1st 'PREPARATION' LAYER OF COLOURED CONCRETE EBC/TROWELLED CONCRETE, 1*mm thick (facilitates application at 2 mm)
*2 mm for exterior floors, applied with notched trowel

1 'PREPARATION' LAYER OF COLOURED CONCRETE EBC/TROWELLED CONCRETE

If 'Lazer': 1 'PREPARATION' LAYER OF EBC/TROWELLED CONCRETE

24H DRYING

2 LAYERS OF EBC/TROWELLED CONCRETE «FRESH INTO FRESH» total thicknes of 1 mm for 2 layers (product rendering is tighter, more effective protection)

24H DRYING

SANDING

5 DAYS FOR DRYING/HARDENING (at 20°C)

PROTECTION

WATER-BASED SEALERS (according to your projet)
MONO AQUA VARNISH SYSTEM
BI AQUA VARNISH FLOOR SYSTEM

7 DAYS FOR DRYING BEFORE PUTTING BACK FURNITURE

OR

CAUTION: ROOM TEMPERATURE MUST BE AT 20°C DURING THE WHOLE DRYING PROCESS

SOLVENT-BASED SEALERS (according to your project)
COLOUR-FREE SOLVANT-BASED SEALER SYSTEM
BI-COMPONENT SOLVENT-BASED VARNISH SYSTEM

2 TO 4 DAYS FOR DRYING BEFORE PUTTING BACK FURNITURE

MAINTENANCE:
To ensure the longevity of your surface, you should treat it with the right products:
- on floors: shampoo for regular maintenance and metallic repair sealer once or twice a year
- on countertops and at showers: diluted black soap for regular maintenance and solid wax as soon as water starts to penetrate the surface.

***FOR BATHROOMS use**
IMPREGNATOR SEALER + COLOUR-FREE SOLVENT-BASED PROTECTOR (SEE SPECIFICATIONS AND SEALERS OVERVIEW) but only AFTER 5 DAYS of drying at 20°C